



D-BELAY STATION 316L

Ref: V40410

Belay Station Type D in 316L stainless steel for outdoor environment / ecotri zinc plated for indoor environment. Two fixing points consisting of hanger Fixe1 at the top end and Fixe 2 at lower end, both of them for M10 / M12 screws. Anchor point with ring. Designed and manufactured in Barcelona-Pyrenees. COMPONENT FEATURES Hanger Fixe 1 - Geometry: Rounded inner edge for less wear on the carabiners. Directs the carabiner for an optimal roof work. Conical Washer. Better control of the tightening torque. Three anti-rotation pins. Optimized surface for full contact. Fixe 1 - Hanger features: For bolts M10 / M12. Weight: 57g (10mm) / 56g (12mm). Breaking strength: 25kN. Material: ecotri zinc plated / 316L stainless steel. Fixe 2 - Hanger features: Contact point with the oval-shaped ring. Increases the lifespan of the ensemble. Conical Washer. Improves the tightening torque. Three anti-rotation pins. For bolts M10 / M12. Breaking strength: 25 kN. Material: available in ecotri zinc plated / 316L stainless steel. Ring features: Ring always present between components for a better workability. TiG welding. Better resistance to corrosion. Inside diameter 33mm. Breaking strength: 25kN. Material: ecotri zinc plated / 316L stainless steel. Features of the 316L stainless steel-chain: TiG welding. Better resistance to corrosion. Reduction of the number of links to three. Less critical points. 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: 316L stainless steel. Features of the ecotri zinc plated-chain: 7mm link-rod diameter. Useful length: 185mm. Breaking strength: 25kN. Material: ecotri zinc plated steel. Are you sure this is your ideal belay station Find it out: <https://www.fixeclimbing.com/configurator/>

Información técnica:

Brand:	Fixe
Diameter:	10mm
Country of origin:	Spain
Color:	Inox
Material:	316L
Breaking Strenght:	25kN
Configurator:	Si